



# COMPACT & N50 PORT SYSTEM FOR COMPACT CAMERA SYSTEM

CAMERA ( HOUSING )	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE			
<b>Sony Cyber-shot</b> <b>DSC-RX100 Mark V</b> ( 17418/17419P / Pro Package )  * 24.70mm (35mm equivalent) * Port is interchangeable for this housing	<b>38702</b> NS0 3.5" Acrylic Wide Angle Dome Port	<b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	35 x 23.3 mm 55-75 mm		
		<b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81302</b> CMC-2	Smallest Subject Size Working Distance	48 x 32mm 80-124 mm		
		<b>83250</b> M67 to Bayonet Mount Converter II <i>(included in all MWC-1 packaging)</i>	<b>83203</b> WWL -C	Lens FOV Converted FOV	84-34° 130-52°		
			<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-34° 130-58° 28-70 mm		
			<b>86201</b> MWL -1	Lens FOV Converted FOV Zoom Range	37-34° 138-128° 65-70 mm		
	<b>Sony Cyber-shot</b> <b>DSC-RX100 Mark VI</b> ( 17421/17421P / Pro Package )  * 24-200mm (35mm equivalent) * Port is interchangeable for this housing	<b>38702</b> NS0 3.5" Acrylic Wide Angle Dome Port	<b>25107</b> M67 Flip Diopter Holder	<b>81202</b> SMC-2	Smallest Subject Size Working Distance	7.5 x 5 mm 34-37 mm	
					<b>81203</b> SMC-3	Smallest Subject Size Working Distance	16 x 10.7 mm 91-103 mm
			<b>38704</b> NS0 Short Port 22 with Bayonet Mount * change part from housing	<b>83203</b> WWL -C	Lens FOV Converted FOV Zoom Range	84-46° 130-70° 24-50 mm	
			<b>83214</b> Bayonet Mount Adaptor for SMC/CMC	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	38 x 25.3 mm 25-95 mm	
				<b>81302</b> CMC-2	Smallest Subject Size Working Distance	48.5 x 32.3 mm 50-160 mm	
			<b>38703</b> NS0 Short Port 25 with Bayonet Mount * change part from housing	<b>86201</b> MWL -1	Lens FOV Converted FOV Zoom Range	40-37° 150-138° 60-65 mm	
<b>Sony Cyber-shot</b> <b>DSC-RX100 Mark VII</b> ( 17424/17424P / Pro Package )  * 24-200mm (35mm equivalent) * Port is interchangeable for this housing	<b>38702</b> NS0 3.5" Acrylic Wide Angle Dome Port	<b>25107</b> M67 Flip Diopter Holder	<b>81202</b> SMC-2	Smallest Subject Size Working Distance	7.5 x 5 mm 34-37 mm		
				<b>81203</b> SMC-3	Smallest Subject Size Working Distance	16 x 10.7 mm 91-103 mm	
		<b>38705</b> NS0 Short Port 17 with Bayonet Mount * change part from housing	<b>83203</b> WWL -C	Lens FOV Converted FOV Zoom Range	84-46° 130-70° 24-30 mm		
		<b>38703</b> NS0 Short Port 25 with Bayonet Mount * change part from housing	<b>86201</b> MWL -1	Lens FOV Converted FOV Zoom Range	37° 138° 65 mm		
			<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-37° 130-64° 28-65 mm		
		<b>83214</b> Bayonet Mount Adaptor for SMC/CMC	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	34 x 22.7 mm 40-85 mm		
	<b>81302</b> CMC-2	Smallest Subject Size Working Distance	43.5 x 29 mm 58-154 mm				
<b>Canon Powershot</b> <b>G5XMKII</b> ( 17331/17331P / Pro Package )  * 24-100mm (35mm equivalent) * Port is interchangeable for this housing	<b>38702</b> NS0 3.5" Acrylic Wide Angle Dome Port	<b>25107</b> M67 Flip Diopter Holder	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	21 x 14 mm 44-72 mm		
				<b>81302</b> CMC-2	Smallest Subject Size Working Distance	21 x 18mm 67-120mm	
		<b>38703</b> NS0 Short Port 25 with Bayonet Mount * change part from housing	<b>83203</b> WWL -C	Lens FOV Converted FOV Zoom Range	84-46° 130-71° 24-50mm		
			<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-46° 130-80° 28-50mm		
		<b>83214</b> Bayonet Mount Adaptor for SMC/CMC	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	40 x 26.7mm 20-72mm		
			<b>81302</b> CMC-2	Smallest Subject Size Working Distance	47 x 31.3mm 33-122mm		
	<b>Canon Powershot</b> <b>G7XMKII</b> ( 17324 NA-G7XII )  * 24-100mm (35mm equivalent) * Port is interchangeable for this housing	<b>38702</b> NS0 3.5" Acrylic Wide Angle Dome Port	<b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	23 x 13.3mm 56-72mm	
			<b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81302</b> CMC-2	Smallest Subject Size Working Distance	31 x 20.7mm 87-122mm	
			<b>83250</b> M67 to Bayonet Mount Converter II <i>(included in all MWC-1 packaging)</i>	<b>86201</b> MWL -1	Lens FOV Converted FOV Zoom Range	37-24° 138-90° 65-100mm	
			<b>38703</b> NS0 Short Port 25 with Bayonet Mount * change part from housing	<b>83203</b> WWL -C	Lens FOV Converted FOV Zoom Range	84-46° 130-71° 24-50mm	
				<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-37° 130-64° 28-65mm	
			<b>83214</b> Bayonet Mount Adaptor for SMC/CMC	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	23 x 13.3mm 45-72mm	
<b>Canon Powershot</b> <b>G7XMKIII</b> ( 17330P / Pro Package )  * 24-100mm (35mm equivalent) * Port is interchangeable for this housing	<b>38702</b> NS0 3.5" Acrylic Wide Angle Dome Port	<b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	23 x 13.3mm 56-72mm		
		<b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81302</b> CMC-2	Smallest Subject Size Working Distance	31 x 20.7mm 87-122mm		
		<b>83250</b> M67 to Bayonet Mount Converter II <i>(included in all MWC-1 packaging)</i>	<b>86201</b> MWL -1	Lens FOV Converted FOV Zoom Range	37-24° 138-90° 65-100mm		
		<b>38703</b> NS0 Short Port 25 with Bayonet Mount * change part from housing	<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-37° 130-64° 28-65mm		
			<b>86201</b> MWL -1	Lens FOV Converted FOV Zoom Range	37-34° 138-128° 65mm		
		<b>83214</b> Bayonet Mount Adaptor for SMC/CMC	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	33 x 22mm 45-72mm		
<b>Canon PowerShot</b> <b>V1 Digital Camera</b> ( 17343 NA-CV1 )  * 16-50mm (35mm equivalent) * Port is interchangeable for this housing	<b>TBD</b> NS0 3.5" Acrylic Wide Angle Dome Port * included in NA-CV1 housing packaging * The minimum focus distance at Tele 50mm is 530mm	<b>38703</b> NS0 Short Port 25 with Bayonet Mount * change part from housing	<b>83203</b> WWL -C	Lens FOV Converted FOV Zoom Range	84-46° 130-71° 24-50mm		
			<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-46° 130-80° 28-50mm		
		<b>83214</b> Bayonet Mount Adaptor for SMC/CMC	<b>81501</b> MFD-1	Smallest Subject Size Working Distance	89 x 59.3 mm 116-1150 mm		
			<b>81302</b> CMC-2	Smallest Subject Size Working Distance	48 x 32 mm 55-125 mm		
			<b>81301</b> CMC-1	Smallest Subject Size Working Distance	38 x 25.4 mm 27-74 mm		
<b>Canon EOS R50</b> with RF-18-45 F4.5-6.3 IS STM Lens ( 17340/17340P / Pro Package )  * Port is interchangeable for this housing	<b>83214</b> Bayonet Mount Adaptor for SMC/CMC		<b>81301</b> CMC-1	Max. Magnification Working Distance	0.8X 44-81mm		
			<b>81302</b> CMC-2	Max. Magnification Working Distance	0.6X 68-140mm		
			<b>81501</b> MFD-1	Max. Magnification Working Distance	0.28X 167-1110mm		
			<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-35° 130-60° 18-45mm		
			<b>83203</b> WWL -C	Lens FOV Converted FOV Working Distance	75-35° 116-52° 18-45mm		
			<b>86201</b> MWL -1	Lens FOV Converted FOV Zoom Range	40-35° 150-130° 38-45mm		
<b>Nikon Z50II</b> with Nikkor Z DX 16-50 Lens ( 17231 NA-Z50II )  * Port is interchangeable for this housing	<b>83214</b> Bayonet Mount Adaptor for SMC/CMC		<b>81301</b> CMC-1	Max. Magnification Working Distance	0.9X 45.5-75mm		
			<b>81302</b> CMC-2	Max. Magnification Working Distance	0.67X 70-130mm		
			<b>83203</b> WWL -C	Lens FOV Converted FOV Zoom Range	84-31.5° 130-49°		
			<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-31.5° 125-55° 20-50mm		
<b>Panasonic Lumix</b> <b>DC-LX100II</b> ( 17717 NA-LX100II )  * 24-75mm (35mm equivalent) * Port is interchangeable for this housing	<b>38702</b> NS0 3.5" Acrylic Wide Angle Dome Port	<b>25107</b> M67 Flip Diopter Holder	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	33.5 x 22.3mm 50-77mm		
				<b>81302</b> CMC-2	Smallest Subject Size Working Distance	47 x 31.3mm 76-130mm	
		<b>38703</b> NS0 Short Port 25 with Bayonet Mount * change part from housing	<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-57° 130-99° 28-40mm		
		<b>38704</b> NS0 Short Port 22 with Bayonet Mount * change part from housing	<b>83203</b> WWL -C	Lens FOV Converted FOV Working Distance	84-72° 130-112° 24-30mm		
			<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-72° 130-125° 28-30mm		
	<b>Panasonic Lumix</b> <b>DC-LX10 (LX10)</b> ( 17714 NA-LX10 )  * 24-72mm (35mm equivalent) * Port is interchangeable for this housing	<b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81302</b> CMC-2	Smallest Subject Size Working Distance	34 x 22.7mm 48-73mm	
			<b>83250</b> M67 to Bayonet Mount Converter II <i>(included in all MWC-1 packaging)</i>	<b>81302</b> CMC-2	Smallest Subject Size Working Distance	45 x 30.7mm 76-128mm	
				<b>83203</b> WWL -C	Lens FOV Converted FOV Zoom Range	70-54° 130-53° 32-72mm	
				<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	58-34° 130-60° 38-72mm	
				<b>86201</b> MWL -1	Lens FOV Converted FOV Zoom Range	37-34° 138-128° 65-72mm	
<b>Panasonic Lumix</b> <b>DC-L10</b> ( 17723 NA-L10 )  * 24-75mm (35mm equivalent) * Port is interchangeable for this housing	<b>38702</b> NS0 3.5" Acrylic Wide Angle Dome Port	<b>25107</b> M67 Flip Diopter Holder	<b>81501</b> MFD-1	Smallest Subject Size Working Distance	108 x 81.2mm 210-1200 mm		
				<b>81301</b> CMC-1	Smallest Subject Size Working Distance	33.5 x 25.2mm 51-72mm	
				<b>81302</b> CMC-2	Smallest Subject Size Working Distance	45.5 x 34.2mm 82-123mm	
		<b>38703</b> NS0 Short Port 25 with Bayonet Mount * change part from housing	<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-57° 130-99° 28-40mm		
		<b>38704</b> NS0 Short Port 22 with Bayonet Mount * change part from housing	<b>83203</b> WWL -C	Lens FOV Converted FOV Working Distance	84-72° 130-112° 24-30mm		
			<b>83202</b> WWL -1B	Lens FOV Converted FOV Zoom Range	75-72° 130-125° 28-30mm		
<b>Olympus Tough TG5/TG6/TG7</b> (with M52 Thread)  * 24-100mm (35mm equivalent) * Port is interchangeable for this housing	<b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>MS2 to M67 Step Up Adaptor Ring + M67 Spacer Ring for SMC/CMC</b> <i>(MS2 is included in all SMC/CMC packaging)</i>	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	19 x 12.7mm 34-78mm		
		<b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81302</b> CMC-2	Smallest Subject Size Working Distance	21 x 14mm 28.5-98mm		
			<b>83203</b> WWL -C	Lens FOV Converted FOV	84-24° 130-37°		
		<b>83214</b> Bayonet Mount Adaptor for SMC/CMC	<b>81301</b> CMC-1	Smallest Subject Size Working Distance	19 x 12.7mm 34-78mm		
<b>Olympus Tough TG5/TG6/TG7</b> (with Bayonet Mount)  * 24-100mm (35mm equivalent) * Port is interchangeable for this housing	<b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC		<b>81302</b> CMC-2	Smallest Subject Size Working Distance	21 x 14mm 28.5-98mm		
<b>Olympus PT-058/PT-059 Underwater Housing</b>	<b>83256</b> M67 to Bayonet Mount Converter for Olympus PT-058/PT-059	<b>83203</b> WWL -C	Lens FOV Converted FOV	84-24° 130-37°			

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended Nautilcam underwater optics based on best underwater optical performance

\* Recommended Porticam